


The Village at Wellard Page 1 of 2

A PEET Limited and Department of Housing Joint Venture Project



PROJECTION: PCG 94 PLANNER: KG



www.cdpaus.com.au

Copyright CDP. No part of this plan may be reproduced in any form without prior consent from CDP. All care has been taken in preparation of this plan but no responsibility is taken for any errors or omissions and is subject to change. Areas and dimensions shown on plan are subject to final survey. Carriageways depicted on plan are diagrammatic only.

LOCAL DEVELOPMENT PLAN PROVISIONS - THE VILLAGE AT WELLARD STAGE 47

The development standards contained in the Local Development Plan (LDP) apply in addition to those development requirements of the City of Kwinana Local Planning Scheme No.2 (LPS2) and any relevant planning policy effective under LPS2 as applicable.

Provisions addressed below relate to Stage 47 within The Village at Wellard Estate, Wellard. The requirements of State Planning Policy 7.3 Residential Design Codes (R-Codes) apply, unless otherwise provided for below.

The following standards represent variations to the R-Codes and constitute 'deemed-to-comply' requirements, pursuant to the R-Codes.

1.	R-CODE VARIATIONS	
a.	Minimum Open Space*:	
	i. R25:	40%
	ii. R30	35%
	iii. R40:	30%

NOTES:

'NB:

- Minimum open space may be reduced to:
 - 40% for R25 lots, subject to the provision of a 30m² Outdoor Living Area.
- 35% for R30 lots, subject to the provisions of a 20m² Outdoor Living Area.
 30% for R40 lots, subject to the provision of a 20m² Outdoor Living Area.
- In all instances, a minimum dimension of 4m is required, with two-thirds of this area uncovered and located behind the street sethack area.

2.	SETBACK PROVISIONS			
		Minimum	Maximum	
a.	Dwelling: i. Primary Street: R25	3.0m	5.0m	
	R30 & R40	2.0m	4.0m	
b.	Garage: i. Primary Street ii. Secondary Street (No Footpath) iii. Secondary Street (With Footpath) Boundary Walls (Parapets):	4.5m Nil 1.5m For all R30 & R40 lots, and lots wi	- - - th a frontage of 11 metres or less,	
		lot boundary walls are permitted to both side boundaries for a maximum length prescribed by the front and rear setback requirements (with the exception of side street boundaries).		
d.	Bushfire Compliance Lots 1784 – 1786 & 1801:	Lots 1784 – 1786 & Lot 1801 require a minimum street setback of 5m to the 'Primary Dwelling Orientation' arrow shown on the Local Development Plan to ensure compliance with the BAL-19 rating provisions of the bushfire management plan prepared by MBS Environmental Titled 'BAL-Assessment Report Stage 47, The Village Wellard.'		

- 3. BUILDING FORM, ORIENTATION & DWELLING FACADE
- a. The design of dwellings shall include an articulated front elevation in the direction of the 'Primary Dwelling Orientation' arrow shown on the Local Development Plan. The front elevation shall consist of at least one major opening to a habitable room overlooking the 'Primary Dwelling Orientation'.
- b. The design of dwellings on applicable lots shall include a side elevation, which has at least one major opening facing the direction of the 'Secondary Dwelling Orientation' arrow shown on the Local Development Plan.

The part of the dwelling which includes the required major opening shall be well articulated and its view not obstructed by visually impermeable fencing.

- c. All dwellings to provide an appropriate, high quality design interface with the surrounding streetscape, through the use of at least three of the following architectural design features:
 - i. Articulation in dwelling façade (i.e. varied wall setbacks);
 - ii. A minimum of two building materials, colours and/or finishes (e.g. render, brick, cladding);
 - iii. Major habitable room openings incorporate large windows to provide surveillance;
 - iv. Roof forms that incorporate gables;
- v. A balcony, portico, or verandah; or
- vi. A built-in planter box.
- d. Where possible, dwellings are to be designed to take advantage of northern solar orientation
- 4. VEHICULAR ACCESS & GARAGES/CARPORTS
- a. All garages are to have doors to enclose them.
- b. Designated garage locations apply to lots identified on the Local Development Plan; this is referencing the side of the lot to which the garage location is recommended. Designated garage locations do not prescribe boundary walls.
- c. Garages are not to be forward of the dwelling alignment. Garages may be aligned with the dwelling, provided they do not exceed the dwelling setback line.
- d. Where lots have a frontage of ≤12 metres, garages may exceed 50% of the primary lot frontage to a maximum of 60% of the primary lot frontage.
- e. Where garages exceed 50% of the primary lot frontage, they shall comply with the following:
 - i. A clear indication of the dwelling entrance.
 - ii. The dwelling entrance shall be the dominant feature of the façade, and shall include a portico or verandah, forward of the dwelling alignment with a minimum depth of 1.5 metres.
 - iii. Garages are to be setback at least 0.5 metres behind the dwelling alignment.
- f. For any single storey dwelling with a frontage ≤10 metres in width and where vehicle access is gained solely from the primary street, only a single width garage/carport (including tandem) is permitted.
- g. Double garages are permitted on lots <10 metres wide where dwellings are two-storeys and where major openings to habitable rooms are provided on the primary street frontage.
- h. For all lots where a footpath adjoins the boundary, the garage must be setback a minimum of 4.5 metres where it adjoins the primary street setback.
- 5. FENCING
- a. Front fences within the primary street setback shall be visually permeable above 0.9 metres, to a maximum height of 1.2 metres above natural ground level.
- b. For secondary street boundaries, fencing shall be visually permeable above 1.2 metres behind the primary street setback, for a minimum length of 3 metres behind the truncation, with a habitable room addressing the street.
- 6. BUSHFIRE MANAGEMENT
- a. The land subject of this LDP is within a bushfire prone area, as designated by the Department of Fire and Emergency Services. Those lots identified on this LDP as being subject to a Bushfire Management Plan require a Bushfire Attack Level (BAL) Assessment prior to construction, in accordance with AS 3959.
- STREET TREE
- a. In accordance with the City's Streetscape Policy, a minimum of one street tree per lot is required (or as agreed with the City). Street trees will be provided by the developer within the road verge and maintained for a minimum of two years until established (or as agreed with the City). Street trees are to be generally located as shown on the Local Development Plan, subject to detailed landscape design and crossover locations. Refer to approved Landscape Plans (available from the City) for detail.
- 8. NOTIFICATION TO PROSPECTIVE PURCHASERS
- The developer is required to give prospective purchasers a complete copy of all the requirements of this Local Development Plan prior to Offer and Acceptance being made.

LOCAL DEVELOPMENT PLAN STAGE 47

The Village at Wellard Page 2 of 2

A PEET Limited and Department of Housing Joint Venture Project

PLAN: PACWE-4-041 REVISION:
DATE: 20/06/2023 DRAWN: JP
PROJECTION: PCG 94 PLANNER: KG

DATUM: AHD



Unit 2, 464 Murray Street Perth WA 6000 (08) 6333 1888 info@cdpaus.com.au www.cdpaus.com.au

Copyright CDP. No part of this plan may be reproduced in any form without prior consent from CDP. All care has been taken in preparation of this pla but no responsibility is taken for any errors or omissions and is subject to change. Areas and dimensions shown on plan are subject to final survey. Considerations of depicted and below of incompants call.